

Safe Work Procedure:

Sprayer coming to Dealership

1. Customer calls service manager requesting their sprayer come to the dealership site for service repairs.
2. Service Manager determines if customer driving sprayer to dealership or if dealership trucking department is hauling sprayer to dealership site.
3. Service Manager informs customer that regardless; the sprayer needs to be drained, rinsed and tank neutralized before dealership works on sprayer or dealership trucking department picks it up.
 - **NOTE: Decontamination should be done in a safe area by washing with water or neutralizing agent or by means recommended by manufacturer of chemical last used.**
4. Service manager confirms the scene is safe for the trucking department to pickup sprayer if customer is not driving it to dealership site.
5. Remind customer to wear appropriate personal protective equipment (PPE) when draining, rinsing, and neutralizing sprayer.

6. If customer driving sprayer to dealership ensure customer parks sprayer in safe area and dealership personnel inspect the sprayer as soon as possible to ensure it has been drained, rinsed and tank neutralized. Also ensure it is not leaking fluid on dealership site and it is parked in a safe location.

- **NOTE: Be aware of Local Bylaws as some jurisdictions do not allow large volumes of sprayer chemicals on premises.**

7. If Dealership Trucking Department is hauling the sprayer inform trucker of work order and confirm safest route. Remember the shortest route is not always the safest/best. Be aware of road construction and seasonal roads.

8. When Trucking Department personnel arrive on site to pick up the sprayer. Ensure the sprayer has been drained, rinsed and tank neutralized. If not immediately contact the dealership service manager for further instructions.

9. When safe to do so, proceed to load sprayer onto trailer. Be sure to follow safe work procedure for loading equipment onto trailer.

10. When securing sprayer to trailer and installing windshield guard ensure three points of contact when climbing onto sprayer and trailer at all times.

11. Drive defensively while hauling loaded sprayer on trailer and be aware of changing road conditions.

12. Once trucking department has arrived at dealership site unload sprayer from trailer and park in designated safe area. Inform service manager sprayer has arrived.

13. Service manager or dealer personnel to inspect sprayer to ensure it is not leaking fluids on dealership site and it is parked in a safe location.

- **NOTE: Keep spray material from contacting skin. If spray material contacts skin, wash off immediately with clean water and detergent or follow manufacturer's instructions for chemical last used.**